

INTATRADE MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31

Printed: 21.03.2022

1. IDENTIFICATION OF SUBSTANCE AND OF THE COMPANY

Product name: Product code: Company:

Phone: Fax: e-mail: Bismuth (III) 2,3-dimethyl-2-butoxide EO04262 INTATRADE Chemicals GmbH Am Winkel 5 06774 Muldestausee, Germany +49 34955/406944 +49 34955/406946 intatrade@intatrade.de

2. HAZARDS IDENTIFICATION

Classification:

GHS label elements

Hazard pictograms Signal word Hazard statements:

Precautionary statements Prevention:

Response:

FLAMMABLE SOLIDS; - Category 2, H228 SKIN CORROSION/IRRITATION; - Category 2, H315 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2, H319 SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY TRACT IRRITATION – Category 3, H335



Warning H228: Flammable solid. H315: Causes skin irritation. H319: Causes serious eye irritation. H335: May cause respiratory irritation. P210: Keep away from heat/sparks/open flames/hot surfaces. -No smoking. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting/handling equipment. P261: Avoiding breathing dusts/aerosols/vapors. P264: Wash skin thoroughly after handling. P271: Use only in outdoors or in a well-ventilated area. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P313 + P332: If skin irritation occurs: Get medical advice/attention. P313 + P337: If eye irritation persists: Get medical advice/attention. P362: Take off contaminated clothing and wash before reuse. P370 + P378: In case of fire: Use alcohol-resistant foam, dry chemical or carbon dioxide for extinction. DO NOT USE WATER.

Storage:	P403 +P233 + P235: Store in a well ventilated area. Keep container tightly closed. Keep cool. P405: Store locked up.
Disposal:	P501: Dispose of contents/ container to an approved wasted disposal plant.
OSHA/HCS status:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Hazards not otherwise classified:	Product reacts with water to produce 2,3-dimethyl-2-butanol.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula:Not available.Synonyms:Bi(DMBX)3.Molecular weight:Not available.CAS-No.:943029-85-4Bismuth(III)2,3-dimethyl-2-butoxide ≥ 98There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

General Advice:	Move out of dangerous area. Call a physician or POISON CONTROL CENTER immediately. Show this safety data sheet to the doctor in
Eye Contact:	attendance. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue rinsing. Call a physician or POISON CONTROL CENTER
Skin Contact:	immediately. Take off contaminated clothing and shoes immediately. Wash off contaminated skin with soap and plenty of water. Get immediate medical attention.
Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER or doctor/physician immediately.
Ingestion:	Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a physician or POISON CONTROL CENTER immediately.
Most Important Symptoms/Effects	Acute And Delayed Potential Acute Health Effects
Eye Contact:	Causes serious eye irritation. Symptoms may include watering, redness, pain with extended exposure resulting in temporary/permanent loss of vision.
Inhalation:	Product is irritating to tissues of the mucous membranes and upper respiratory tract. Exposure may be expected to produce symptoms ranging from coughing, shortness of breath, headache and nausea.
Skin Contact:	Skin contact with this product may be expected to cause irritation. Symptoms may include burning, itching, pain, redness and swelling.
Ingestion:	May be harmful if swallowed. Product is irritating to the tissues of the mouth, throat, esophagus and digestive tract.

Chronic Symptoms:	On contact with water, this product produces 2,3-dimethyl-2-butanol which may produce a chronic effect on the Central Nervous System (CNS).
Indication of Immediate Medical Att	tention and Special Treatment Needed, If Necessary
Notes to Physician:	Treat symptomatically.
Specific Treatments:	No specific treatment.
Protection of First Responders:	No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. See toxicological information (Section 11)

5. FIRE FIGHTING MEASURES

General Hazards: Suitable Extinguishing Media:	None identified. THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY CHEMICAL POWDER PRESSURIZED WITH NITROGEN. Vermiculite,
Unsuitable Extinguishing Media:	sand, dry chemical or carbon dioxide (CO ₂) may also be used. DO NOT USE WATER OR FOAM as product reacts with water to
Unusual Fire and Explosion Hazards:	produce flammable liquids and vapors upon contact with water. This material reacts with water to produce 2,3-dimethyl-2-butanol. Product runoff to sewer may create a fire or explosion hazard. 2,3- dimethyl-2-butanol vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an ignition source and flashback. Do not cut, grind, drill or weld on or near the container (even empty) of this product because an explosion may result. Keep away from heat, sparks and flame.
Product of Combustion: Protection of Firefighters:	Carbon oxides (COX), bismuth oxide. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid breathing dust, aerosols or vapors. Fire-fighters should wear appropriate protection equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.
Personal Precautions, Protective E	Equipment and Emergency Procedures
For Non-emergency Personnel:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid the formation and inhalation of dusts and aerosols. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.
For Emergency Responders:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Environmental Precautions:	Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for Containment	
Small Spill: Large Spill:	Eliminate all ignition sources. Move containers from spill area. Contain and collect spillage with non-combustible, dry binding material e.g. sand, earth, vermiculite or diatomaceous earth and place in dry container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Avoid allowing the spilled material to get wet or using water to clean up spillages or residues, unless the quantity remaining is very small. Use spark-proof tools and explosion-proof equipment. Eliminate all ignition sources. Move containers from spill area.
	Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid allowing the spilled
5004060	

material to get wet or using water to clean up spillages or residues, unless the quantity remaining is very small. Use spark-proof tools and explosion-proof equipment. Contain and collect spillage with noncombustible, dry binding material e.g. sand, earth, vermiculite or diatomaceous earth and place in dry container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated

absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. HANDLING AND STORAGE

Precautions:	Product is air/moisture sensitive. Handle under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Avoid contact with skin, eyes and clothing. Avoid the formation of dusts. Avoid inhalation of dusts, aerosols, and vapors. Do not ingest. Provide adequate ventilation. Keep away from sources of ignition – No smoking.
Protective Measures:	Protect against electrostatic charges. Use explosion-proof electrical/ventilating/lighting/handling equipment. Use only non-sparking tools and equipment. Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
General Occupational Hygiene:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking or smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Safe Storage Conditions:	Product is air/moisture sensitive. Store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from air, moisture, water, heat, sparks and open flames. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials noted above and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Introductory Remarks:	These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.
Occupational Exposure Limits:	Product contains no substances with occupational exposure limit values.
Engineering Controls:	Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.
Environmental Exposure Controls:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual Protection Measures	·
Hygiene Measures:	Avoid all unnecessary exposure. Wash all exposed skin (hands, forearms and face) thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do

E004262

	not inhale dusts, vapors or mists. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/Face Protection:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.
Skin Protection	
Hand Protection:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical- resistant gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. For full contact, use Neoprene or nitrile rubber.
Other Skin Protection:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory Protection:	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Color: Odor: Odor Threshold: Melting Point: Boiling Point: Flash Point: Auto-ignition temperature: Relative Density: Vapor Pressure: Vapor Density:	Solid (low melting point). Clear (colorless). No data available. No data available.
Vapor Pressure:	No data available.
Water Solubility:	Reacts with water to produce flammable liquid and vapors.
VOC Content: No data available. VOCs are calculated following the requirements under 40 CFR, Part 59, Subpart C for Consumer Products and Subpart D for Architectural Coatings.	

10. STABILITY AND REACTIVITY

Reactivity:	This product reacts with water to produce 2,3-dimethyl-2-butanol, a flammable liquid/vapor mixture.	
Chemical Stability:	This product is stable when stored under a dry, inert atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended. This product is not sensitive to impact.	
Conditions to Avoid:	Keep away from moisture, heat and sources of ignition. Avoid extremes of temperature and direct sunlight.	
Incompatible Materials:	Water/moisture, air and compounds containing active hydrogen such as alcohols and acids. Strong oxidizing agents.	
Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition		
Possibility of Hazardous Reactions	 products should not be produced. In contact with water, product releases 2,3-dimethyl-2-butanol, a highly flammable liquid/vapor mixture. Hazardous decomposition products formed under fire conditions: carbon oxides and bismuth oxide fumes. In the event of a fire: see section 5. Under normal conditions of storage and use noted above, hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. In contact with water, product produces 2,3-dimethyl-2-butanol, a flammable liquid/vapor mixture. Vapors may form an explosive mixture with air. 	

11. TOXICOLOGICAL INFORMATION

Information on Toxicological Effects Acute Toxicity:

Acute Toxicity:	Product may be irritating to the tissue of the mucous membranes and upper respiratory tract. Reaction of the product with water in the body will produce 2,3-dimethyl-2-butanol which may lead to symptoms associated with alcohol consumption and/or poisoning. Symptoms may include depression of CNS and narcosis.
Irritation/Corrosion:	Product is irritating to the skin and seriously irritating to the eyes.
Sensitization:	No specific data available.
Germ Cell Mutagenicity:	No specific data available.
Carcinogenity	·
IĂRC:	No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH:	No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
NTP:	No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
OSHA:	No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
Reproductive Toxicity:	This product is not expected to cause reproductive or developmental effects.
Teratogenicity:	No specific data available.
Specific Target Organ Toxicity:	Respiratory tract irritation/damage through
(single exposure) Specific Target Organ Toxicity	irritation/corrosion of the mucous membranes.
(repeated exposure):	No specific data available.
Aspiration Hazard:	No specific data available.
Information on the likely	
routes of exposure.	Inhalation, skin, eyes, ingestion.
Additional Information:	To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

Numerical Measures of Toxicity	
Toxicity to Fish:	No specific data available.
Toxicity to daphnia and other	
aquatic invertebrates:	No specific data available.
Toxicity to algae:	No specific data available.
Persistence and Degradability	
Biodegradability:	No specific data available.
Bioaccumulative potential:	No specific data available.
Mobility in soil:	No specific data available.
Other Adverse Effects:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods	
Product:	Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.
Contaminated Packaging:	Empty containers retain product residue (dusts, aerosols, vapors and gases) and can be dangerous. DO NOT EXPOSE SUCH CONTAINERS TO MOISTURE, HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

14. TRANSPORT INFORMATION

	DOT	IMDG	ΙΑΤΑ
UN Number	UN 3181	UN 3181	UN 3181
UN Proper Shipping Name	Metal salts of organic compounds, flammable, n.o.s. (Bismuth(III)2,3- dimethyl-2-butoxide)		
Transport Hazard Classes	4.1	4.1	4.1
Packing Group	111	111	111
Environmental Hazards	-	-	-
Additional Information	-	EMS-No: F-A, S-G	-
Special Precautions for User:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
Transporting in Bulk According to Annex II of MARPOL 73/78			
and the IBC Code:	Not applicab	le.	

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act):	This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.
SARA 302 Components	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313 Components	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

16. OTHER INFORMATION

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Intatrade Chemicals GmbH shall not be held liable for any damage resulting from handling or from contact with the above product.